



Dell EMC PowerSwitch N1100 Series Switches

Fully managed 1/10GbE Layer 2 switching with Open Networking capabilities

The N1100 switch series offers a power-efficient Gigabit Ethernet (GbE) network-access switching solution with integrated 1GbE and 10GbE uplinks. With high-performance capabilities and wire-speed performance, utilizing a non-blocking architecture to easily handle unexpected traffic loads, the switches offer simple management and scalability via a 1Gbps (full-duplex) high availability stacking architecture that allows management of up to four switches from a single IP address. Fanless operation on select models, and features such as Energy-Efficient Ethernet and short cable detection provide energy efficiency to help decrease power and cooling costs.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/10GbE switching solution with up to 24 PoE/PoE+ ports. PoE power budgets up to 375W deliver clean power to network devices such as wireless access points (APs), Voiceover-IP (VoIP) handsets, video conferencing systems and security cameras.

Leverage familiar tools and practices

All N-Series switches include Dell EMC Networking OS 6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. One common command line interface (CLI) and graphic user interface (GUI) using a well-known command language gets skilled network administrators productive quickly. The N1100 switch series also supports the Open Network Install Environment (ONIE), enabling installation of alternate network operating systems.

Deploy with confidence at any scale

N1100 series switches help create performance assurance with a data rate up to 176Gbps (full duplex) and a forwarding rate up to 164Mpps. Scale easily by stacking

with 10GbE ports. Switch stacks of up to 192 1GbE ports can be managed from a single screen using the highly available stacking architecture for high-density aggregation with seamless redundant availability. N-Series switches help provide certainty with a lifetime warranty that covers software upgrades, hardware repair or replacement, and optics and cables purchased with the switch. Details at Dell.com/LifetimeWarranty.*

Hardware, performance and efficiency

- Up to 48 line-rate GbE RJ45 ports and four integrated 10GbE SFP+ ports.
- Up to 12 PoE/PoE+ ports without an optional external power supply.
- Up to 192 1GbE ports in a 4-unit stack for high-density, high-availability in IDFs, MDFs and wiring closets.
- Non-stop forwarding and fast failover in stack configurations (24- and 48-port models only).
- Energy-Efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Fresh Air compliance for operation in environments up to 113°F (45°C) helps reduce cooling costs in temperature-constrained deployments.

Deploying, configuring and managing

- USB auto-configuration rapidly deploys the switch without setting up complex TFTP configurations or sending technical staff to remote offices.
- Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell OpenManage Network Manager), Telnet or serial connection.

*Select Networking products carry a Lifetime Limited Warranty with Basic Hardware Service (repair or replacement) for life. Repair or replacement does not include troubleshooting, configuration, or other advanced service provided by Dell EMC ProSupport.

- Deploy, monitor and troubleshoot via integration with HiveManager cloud or on-premise management
- Private VLAN extensions and Private VLAN Edge support.
- AAA authorization, TACACS+ accounting and RADIUS support for comprehensive secure access support.
- Authentication tiering allows network administrators to tier port authentication methods such as 802.1x, MAC Authentication
- Bypass and Captive Portal in priority order so that a single port can provide flexible access and security.
- Remote Switch Port Analyzer (RSPAN) monitors ports across a Layer 2 domain without costly dedicated network taps.

Product	Description
N1100 series	N1108T-ON: 8x 10/100/1000Mbps half/full duplex RJ45 ports, 2x GbE RJ45 and 2x GbE SFP interfaces, 1 RU half-width form factor, fanless operation N1108EP-ON: 8x 10/100/1000Mbps half/full duplex ports, 2x GbE RJ45 and 2x GbE SFP interfaces, 8xPoE/PoE+, 137W PoE power budget RJ45, FastPoE, Perpetual PoE, 1 RU half-width N1124T-ON: 24x 10/100/1000Mbps half/full duplex RJ45 ports, 4x SFP/SFP+ 1/10GbE ports, 1 RU switch form factor, fanless operation N1124P-ON: 24x 10/100/1000Mbps half/full duplex ports, 4x SFP/SFP+ 1/10GbE ports, 12xPoE/PoE+ ports 190W PoE power budget, 1 RU switch form factor N1148T-ON: 48x 10/100/1000Mbps half/full duplex RJ45 ports, 4x SFP+ 10GbE ports, 1 RU, fanless N1148P-ON: 48x 10/100/1000Mbps half/full duplex ports, 4x SFP/SFP+ 1/10GbE ports, 24xPoE/PoE+, 375W PoE power budget, 1 RU switch form factor
Power cords	+ C13 to NEMA 5-15, 3M C13 to C14, 2M C15 to NEMA 5-15, 2M (C15 for PoE N-Series only)
Optics (optional)	Transceiver, SFP, 1000BASE-T Transceiver, SFP, 1000BASE-SX, 850nm wavelength, up to 550m reach Transceiver, SFP, 1000BASE-LX, 1310nm wavelength, up to 10km reach Transceiver, SFP, 1000BASE-ZX, 1550nm wavelength, up to 80km reach Transceiver, SFP+, 10GbE, SR, 850nm wavelength, up to 300m reach Transceiver, SFP+, 10GbE, LR, 1310nm wavelength, up to 10km reach Transceiver, SFP+, 10GbE, ER, 1550nm wavelength, up to 40km reach
Cables (optional)	Dell Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct

Technical specifications

Physical

4x integrated front 10GbE SFP+ dedicated ports, 2x 10GbE can be used as stacking ports (24 and 48-port models), 2x 1GbE SFP links (8-port models)

USB (Type A) port for configuration via USB flash drive

Auto-negotiation for speed and flow control

Auto MDI/MDIX, port mirroring

Flow-based port mirroring

Broadcast storm control

Energy-Efficient Ethernet per port settings

Redundant variable speed fans

Air flow: I/O to power supply; Pass through POE (N1108EP-ON)

External power adapter: 137W of POE power (N1108EP-ON)

Integrated power supply: 24W AC (N1108T-ON); 40W AC (N1124T-ON); 250W AC (N1124P-ON);

60W AC (N1148T-ON); 500W AC (N1148P-ON)

Micro USB Console port (Micro USB to USB cable included)

Dual firmware images on-board

Switching engine model: Store and forward;

Chassis

Size (H x W x D) in inches:

N1108T-ON, N1108EP-ON: 1.62 x 8.23 x 8.86

N1124T-ON, N1124P-ON, N1148T-ON,

N1148P-ON: 1.75 x 17 x 10

N1108EP-ON 280W PS 1.69x3.94x7.87

Approximate weight: N1108EP-ON 4lbs, 1.81kg

N1108T-ON 3.54lbs, 1.61kg

N1124T-ON 6.72lbs, 3.05kg N1124P-ON

8.33lbs, 3.78kg N1148T-ON 8.33lbs, 3.78kg

N1148P-ON 9.19lbs, 4.17kg

N1108EP-ON 280W PowerSupply 2.0lbs, 0.91kg

Rack mounting kit with 2 mounting

brackets, bolts and cage nuts

1RU tray to accommodate two half rack width

switches (kit includes L-brackets for 800mm deep rack/ cabinet)

Environmental

Power supply efficiency: 80% or better in all operating modes

Max. thermal output (BTU/hr): 66.53 (N1108EP-

ON), 35.72 (N1108T-ON), 65.85 (N1124T-ON),

851.66 (N1124P-ON), 102.98 (N1148T-ON),

1566.15 (N1148P-ON)

Power consumption max (watts)

19.51 (N1108EP-ON), 10.47 (N1108T-ON), 19.3 (N1124T-ON), 249.6 (N1124P-ON), 30.18 (N1148T-ON), 459 (N1148P-ON)

Operating temperature:

32° to 113°F (0° to 45°C) (N1108EP-ON, N1108T-ON, N1124T-ON, N1124P-ON, N1148T-ON, N1148P-ON)

Operating humidity: 95%

Storage temperature: -40° to 149°F (-40° to 65°C)

Storage relative humidity: 85%

Performance

MAC addresses: 16K

Switch fabric capacity: 24Gbps (N1108T-ON and N1108EP-ON), 128Gbps (N1124T-ON and N1124P-ON), 176Gbps (N1148T-ON and N1148P-ON)

Forwarding rate: 18Mpps (N1108T-ON and N1108EP-ON), 96Mpps (N1124T-ON and N1124P-ON), 132Mpps (N1148T-ON and N1148P-ON)

Link aggregation: 64 LAG groups, 144 dynamic ports per stack, 8 member ports per LAG

Queues per port: 8

Line-rate Layer 2 switching: All (non-blocking)

Flash memory: 1GB

2 Dell EMC PowerSwitch N1100 Series Switches

© 2019 Dell Inc. or its subsidiaries.

Technical specifications

Packet buffer memory: 1.5MB (N1108T-ON and N1108EP-ON), 2MB (N1124T-ON and N1124PON), 4MB (N1148T-ON and N1148P-ON)

CPU memory: 1GB

VLANs supported: 512

Protocol-based VLANs: Supported

ARP entries: 2,048 (IPv4)/512 (IPv6)

NDP entries: 400

Access control lists (ACL): Supported

MAC and IP-based ACLs: Supported

Time-controlled ACLs: Supported

Max ACL rules (system-wide): 4K

Max configurable rules per list: 1023

Max ACL rules per interface and direction (IPv4/L2): 1023

Max ACL rules per interface and direction (IPv6): 1021 ing/253 egr

Max ACL logging rules (system-wide): 128

Max number of ACLs: 100

Max VLAN interfaces with ACLs applied: 24

IEEE Compliance

802.1AB LLDP

Dell Voice VLAN

Dell ISDP (inter-operates with devices running CDP)

802.1D Bridging, Spanning Tree

802.1p Ethernet Priority (User Provisioning and Mapping)

Dell Adjustable WRR and Strict Queue Scheduling

802.1Q VLAN Tagging, Double VLAN Tagging, GVRP

802.1S Multiple Spanning Tree (MSTP)

802.1v Protocol-based VLANs

802.1W Rapid Spanning Tree (RSTP)

Dell RSTP-Per VLAN (compatible with Cisco's RPVST+)

Dell Spanning tree optional features: STP root guard, BPDU guard, BPDU filtering

802.1X Network Access Control, Auto VLAN

802.2 Logical Link Control

802.3 10BASE-T

802.3ab Gigabit Ethernet (1000BASE-T)

802.3ac Frame Extensions for VLAN Tagging

802.3ad Link Aggregation with LACP

802.3ae 10 Gigabit Ethernet (10GBASE-X)

802.3af PoE (N1108EP-ON, N1124P-ON, N1148P-ON)

802.3at PoE+ (N1108EP-ON, N1124P-ON, N1148P-ON)

802.3AX LAG Load Balancing

802.3az Energy Efficient Ethernet (EEE)

802.3u Fast Ethernet (100BASE-TX) on Management Ports

802.3x Flow Control

802.3z Gigabit Ethernet (1000BASE-X)

ANSI LLDP-MED (TIA-1057)

MTU 9,216 bytes

RFC compliance and additional features

General Internet protocols

General Internet protocols are supported. For a detailed list, please contact your Dell EMC representative.

General IPv4 protocols

General IPv4 protocols are supported. For a detailed list, please contact your Dell EMC representative.

General IPv6 protocols

General IPv6 protocols are supported. For a detailed list, please contact your Dell EMC representative.

Multicast

2932 IPv4 MIB 4541 IGMP v1/v2/v3 Snooping and Querier
IEEE 802.1ag draft 8.1—Connectivity Fault Management

Quality of service

2474 DiffServ Field
2475 DiffServ Architecture
2597 Assured Fwd PHB
Dell L4 Trusted Mode (TCP/UDP)
Dell UDLD
Dell Flow Based QoS Services Mode (IPv4/IPv6)
Dell Port Based QoS Services Mode

Network management and security

1155 SMIv1
1157 SNMPv1
1212 Concise MIB Definitions
1213 MIB-II
1215 SNMP Traps
1286 Bridge MIB
1442 SMIv2
1451 Manager-to-Manager MIB
1492 TACACS+
1493 Managed Objects for Bridges MIB
1573 Evolution of Interfaces
1612 DNS Resolver MIB Extensions
1643 Ethernet-like MIB
1757 RMON MIB
1867 HTML/2.0 Forms with File Upload Extensions
1901 Community-based SNMPv2
1907 SNMPv2 MIB
1908 Coexistence Between SNMPv1/v2
2011 IP MIB
2012 TCP MIB
2013 UDP MIB
2068 HTTP/1.1
2096 IP Forwarding Table MIB
2233 Interfaces Group using SMIv2
2246 TLS v1
2271 SNMP Framework MIB
2295 Transport Content Negotiation
2296 Remote Variant Selection
2346 AES Ciphersuites for TLS
2576 Coexistence Between SNMPv1/v2/v3
2578 SMIv2
2579 Textual Conventions for SMIv2
2580 Conformance Statements for SMIv2
2613 RMON MIB
2618 RADIUS Authentication MIB
2620 RADIUS Accounting MIB
2665 Ethernet-like Interfaces MIB
2674 Extended Bridge MIB
2737 ENTITY MIB
2818 HTTP over TLS
2819 RMON MIB (groups 1, 2, 3, 9)
2863 Interfaces MIB
2865 RADIUS
2866 RADIUS Accounting
2868 RADIUS Attributes for Tunnel Prot.
2869 RADIUS Extensions
3410 Internet Standard Mgmt. Framework
3411 SNMP Management Framework

3412 Message Processing and Dispatching
3413 SNMP Applications
3414 User-based security model
3415 View-based control model
3416 SNMPv2
3418 SNMP MIB
3577 RMON MIB
3580 802.1X with RADIUS
3737 Registry of RMOM MIB
4086 Randomness Requirements
4113 UDP MIB
4251 SSHv2 Protocol
4252 SSHv2 Authentication
4253 SSHv2 Transport
4254 SSHv2 Connection Protocol
4419 SSHv2 Transport Layer Protocol
4521 LDAP Extensions
4716 SECSh Public Key File Format
6101 SSL
Dell Enterprise MIB supporting routing features draft-ietfhubmib-etherif-mibv3-00.txt (Obsoletes RFC 2665)
Dell LAG MIB Support for 802.3ad Functionality
Dell sflow version 1.3 draft 5
Dell 802.1x Monitor Mode
Dell Custom Login Banners
Dell Dynamic ARP Inspection
Dell IP Address Filtering
Dell Tiered Authentication
Dell RSPAN
Dell Python Scripting
Dell Support Assist

Regulatory, environment and other compliance

Safety and emissions

Australia/New Zealand: ACMA RCM Class A
Canada: ICES Class A; cUL
China: CCC Class A; NAL
Europe: CE Class A
Japan: VCCI Class A
USA: FCC Class A; NRTL UL; FDA 21 CFR 1040.10 and 1040.11
Eurasia Customs Union: EAC
Germany: GS mark
Product meets EMC and safety standards in many countries inclusive of USA, Canada, EU, Japan, China. For more country-specific regulatory information and approvals, please see your Dell representative.

Immunity

EN 61000-4-5: Surge

RoHS

Product meets RoHS compliance standards in many countries inclusive of USA, EU, China, and India. For more country-specific RoHS compliance information, please see your Dell EMC representative.
EU WEEE
EU Battery Directive
REACH

Energy

Japan: JEL
Certifications (available or coming soon)
Available with US Trade Agreements Act (TAA) compliance.
N-Series products have the necessary features to support a PCI-compliant network topology.

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize

Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at DellEMC.com/Services

Learn more at DellEMC.com/Networking